

1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Type:	Thinners/ Solvents	Emergency Contact:	Chemtrec
Product Name:	<b>RADIO-TV CEMENT SOLVENT</b>	Phone:	<b>(800) 424-9300</b>
Part Number(s):	<b>10-312</b> <b>10-320</b> <b>10-321</b> <b>10-321-4G</b>		

#### SECTION 2. HAZARD(S) IDENTIFICATION

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

#### Label elements



#### Signal word

Danger

#### Hazard statement

Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

### SECTION 2. HAZARD(S) IDENTIFICATION (CONTINUED)

#### Precautionary statement

##### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.

##### Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

##### Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

##### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

##### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

##### Supplemental information

50% of the mixture consists of component(s) of unknown acute inhalation toxicity. 20% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 20% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-PROPANONE		67-64-1	30.0229
BENZENE, METHYL-		108-88-3	30.0229
ACETIC ACID ETHYL ESTER		141-78-6	20.0153
ACETIC ACID, BUTYL ESTER		123-86-4	20.0153

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 4. FIRST-AID MEASURES

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### SECTION 5. FIRE-FIGHTING MEASURES

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 5. FIRE-FIGHTING MEASURES (CONTINUED)

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.  
**General fire hazards** Highly flammable liquid and vapor.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 7. HANDLING AND STORAGE

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

**Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

##### Occupational exposure limits

##### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup>
ACETIC ACID ETHYL ESTER (CAS 141-78-6)	PEL	1000 ppm 1400 mg/m <sup>3</sup>
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)	PEL	400 ppm 710 mg/m <sup>3</sup> 150 ppm



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

### SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

## Product Name: RADIO-TV CEMENT SOLVENT

### SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION (CONTINUED)

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE, METHYL- (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
ACETIC ACID ETHYL ESTER (CAS 141-78-6)	TWA	400 ppm
	ACETIC ACID, BUTYL ESTER (CAS 123-86-4)	STEL
TWA		150 ppm
BENZENE, METHYL- (CAS 108-88-3)	TWA	20 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup>
		250 ppm
ACETIC ACID ETHYL ESTER (CAS 141-78-6)	TWA	1400 mg/m <sup>3</sup>
		400 ppm
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)	STEL	950 mg/m <sup>3</sup>
	TWA	200 ppm
BENZENE, METHYL- (CAS 108-88-3)	STEL	710 mg/m <sup>3</sup>
	TWA	150 ppm
BENZENE, METHYL- (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>
	TWA	150 ppm
BENZENE, METHYL- (CAS 108-88-3)	TWA	375 mg/m <sup>3</sup>
		100 ppm



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION (CONTINUED)**

**Biological limit values**

**ACGIH Biological Exposure Indices Components Value**

Components	Value	Determinant	Specimen	Sampling Time
2-PROPANONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

**ACGIH Biological Exposure Indices Components Value**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, METHYL- (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

BENZENE, METHYL- (CAS 108-88-3) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

BENZENE, METHYL- (CAS 108-88-3) Skin designation applies.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>		<b>Relative density</b>	Not available.
<b>Physical state</b>	Liquid.	<b>Solubility(ies)</b>	
<b>Form</b>	Liquid.	<b>Solubility (water)</b>	Not available.
<b>Color</b>	CLEAR	<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Odor</b>	SOLVENT	<b>Auto-ignition temperature</b>	848.9 °F (453.83 °C) estimated
<b>Odor threshold</b>	Not available.	<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not available.	<b>Viscosity</b>	Not available.
<b>Melting point/freezing point</b>	-128.34 °F (-89.08 °C) estimated	<b>Other information</b>	
<b>Initial boiling point and boiling range</b>	195.11 °F (90.62 °C) estimated	<b>Density</b>	7.14 lbs/gal
<b>Flash point</b>	0 °F (-17.8 °C)	<b>Explosive properties</b>	Not explosive.
<b>Evaporation rate</b>	Not available.	<b>Flammability class</b>	Flammable IB estimated
<b>Flammability (solid, gas)</b>	Not applicable.	<b>Oxidizing properties</b>	Not oxidizing.
<b>Upper/lower flammability or explosive limits</b>		<b>Percent volatile</b>	100.08 % estimated
<b>Flammability limit - lower (%)</b>	1.8 % estimated	<b>Specific gravity</b>	0.86
<b>Flammability limit - upper (%)</b>	9.3 % estimated	<b>VOC (Weight %)</b>	70.05 % estimated
<b>Explosive limit - lower (%)</b>	Not available.		
<b>Explosive limit - upper (%)</b>	Not available.		
<b>Vapor pressure</b>	131.87 hPa estimated		
<b>Vapor density</b>	Not available.		

#### SECTION 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Nitrates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Information on likely routes of exposure

<b>Inhalation</b>	Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics**      Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

##### Information on toxicological effects

**Acute toxicity**      Toxic if inhaled. Harmful if swallowed. Narcotic effects.

Components	Species	Test Results
2-PROPANONE (CAS 67-64-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
<b>Oral</b>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
ACETIC ACID ETHYL ESTER (CAS 141-78-6)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	16000 ppm, 6 Hours
LD50	Mouse	1500 ppm, 4 Hours
	Rabbit	2500 ppm, 4 Hours
	Rat	4000 ppm, 4 Hours



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)**

<b>Oral</b>			
LD50	Mouse		0.44 g/kg
	Rabbit		4.9 g/kg
	Rat		11.3 ml/kg
			5.6 g/kg

ACETIC ACID, BUTYL ESTER (CAS 123-86-4)

**Acute**

**Inhalation**

LC50	Wistar rat		160 mg/l, 4 Hours
------	------------	--	-------------------

**Oral**

LD50	Rat		14000 mg/kg
------	-----	--	-------------

BENZENE, METHYL- (CAS 108-88-3)

**Acute**

**Dermal**

LD50	Rabbit		12124 mg/kg
			14.1 ml/kg

**Inhalation**

LC50	Mouse		5320 ppm, 8 Hours
			400 ppm, 24 Hours
	Rat		26700 ppm, 1 Hours
			12200 ppm, 2 Hours
			8000 ppm, 4 Hours

**Oral**

LD50	Rat		2.6 g/kg
------	-----	--	----------

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)**

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**  
 BENZENE, METHYL- (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**  
 Not listed.

**Reproductive toxicity** Suspected of damaging the unborn child.

**Specific target organ toxicity - single exposure** May cause drowsiness and dizziness.

**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
<b>2-PROPANONE (CAS 67-64-1)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
<b>ACETIC ACID ETHYL ESTER (CAS 141-78-6)</b>		
<b>Aquatic</b>		
Fish	LC50	Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours
<b>ACETIC ACID, BUTYL ESTER (CAS 123-86-4)</b>		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours
<b>BENZENE, METHYL- (CAS 108-88-3)</b>		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

### Product Name: RADIO-TV CEMENT SOLVENT

#### SECTION 12. ECOLOGICAL INFORMATION (CONTINUED)

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

##### Bioaccumulative potential

###### Partition coefficient n-octanol / water (log Kow)

2-PROPANONE	-0.24
ACETIC ACID ETHYL ESTER	0.73
ACETIC ACID, BUTYL ESTER	1.78
BENZENE, METHYL-	2.73

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### SECTION 13. DISPOSAL CONSIDERATIONS

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 14. TRANSPORTATION INFORMATION**

**DOT**

**UN number** UN1993  
**UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (ACETONE - TOLUENE)  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**ERG number** 128  
DOT information on packaging may be different from that listed.

**DOT**



**General information**

IMDG Regulated Marine Pollutant.



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 15. REGULATORY INFORMATION**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

2-PROPANONE (CAS 67-64-1)	Listed.
ACETIC ACID ETHYL ESTER (CAS 141-78-6)	Listed.
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)	Listed.
BENZENE, METHYL- (CAS 108-88-3)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
BENZENE, METHYL-	108-88-3	30.0229

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE, METHYL- (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

2-PROPANONE (CAS 67-64-1) 6532



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

### SECTION 15. REGULATORY INFORMATION (CONTINUED)

BENZENE, METHYL- (CAS 108-88-3)	6594
<b>Drug Enforcement Administration (DEA). List 1 &amp; 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))</b>	
2-PROPANONE (CAS 67-64-1)	35 %WV
BENZENE, METHYL- (CAS 108-88-3)	35 %WV
<b>DEA Exempt Chemical Mixtures Code Number</b>	
2-PROPANONE (CAS 67-64-1)	6532
BENZENE, METHYL- (CAS 108-88-3)	594

#### US state regulations

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

2-PROPANONE (CAS 67-64-1)  
BENZENE, METHYL- (CAS 108-88-3)

**US. Massachusetts RTK - Substance List**

2-PROPANONE (CAS 67-64-1)  
ACETIC ACID ETHYL ESTER (CAS 141-78-6)  
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)  
BENZENE, METHYL- (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

2-PROPANONE (CAS 67-64-1)  
ACETIC ACID ETHYL ESTER (CAS 141-78-6)  
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)  
BENZENE, METHYL- (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-PROPANONE (CAS 67-64-1)  
ACETIC ACID ETHYL ESTER (CAS 141-78-6)  
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)  
BENZENE, METHYL- (CAS 108-88-3)

**US. Rhode Island RTK**

2-PROPANONE (CAS 67-64-1)  
ACETIC ACID ETHYL ESTER (CAS 141-78-6)  
ACETIC ACID, BUTYL ESTER (CAS 123-86-4)  
BENZENE, METHYL- (CAS 108-88-3)



1801 Morgan Street  
 Rockford, IL 61102  
 Phone: (815) 968-9661  
 Fax: (815) 968-9731  
 www.gcelectronics.com

MSDS Number: 102  
 Revision Date: 08/13/2015  
 Supersedes Date: 07/17/2012

**SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

**SECTION 15. REGULATORY INFORMATION (CONTINUED)**

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

BENZENE, METHYL- (CAS 108-88-3) Listed: January 1, 1991

**US - California Proposition 65 - CRT: Listed date/Female reproductive toxin**

BENZENE, METHYL- (CAS 108-88-3) Listed: August 7, 2009

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**SECTION 16. OTHER INFORMATION**

<b>Issue date</b>	07-20-2015
<b>Revision date</b>	07-21-2015
<b>Version #</b>	02
<b>HMIS® ratings</b>	Health: 3* Flammability: 3 Physical hazard: 0
<b>NFPA ratings</b>	Health: 3 Flammability: 3 Instability: 0



1801 Morgan Street  
Rockford, IL 61102  
Phone: (815) 968-9661  
Fax: (815) 968-9731  
www.gcelectronics.com

MSDS Number: 102  
Revision Date: 08/13/2015  
Supersedes Date: 07/17/2012

## **SAFETY DATA SHEET**

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

**Product Name: RADIO-TV CEMENT SOLVENT**

---

### **SECTION 17. OTHER INFORMATION**

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application.

NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.